

SPECIFICATION



DIMENSIONS		
Overall length Overall width Overall height Wheelbase Road clearance Seat height Curb mass ZX400S Fuel tank capacity	1,990 mm 765 mm 1,110 mm 1,380 mm 135 mm 800 mm 189 kg (IDN) 15 litres	
PERFORMANCE		
Max. power	55.0 kW {75 PS} / 14,500 min ⁻¹	
Max. power with Ram Air	56.7 kW {77 PS} / 14,500 min ⁻¹	
Max. torque	37.6 N·m {3.8 kg <i>f</i> ·m} / 12,500 min ⁻¹	
ENGINE		
Type Valve system Bore x Stroke	Liquid-cooled, 4-stroke In-Line Four DOHC, 16 valves 57.0 x 39.1 mm	
Displacement	399 cm ³	
Compression ratio Fuel supply Lubrication system Starting system Ignition system	12.3:1 Fuel injection: ø34 mm x 4 Forced lubrication, wet sump Electric Digital	
DRIVETRAIN		
Driving system Transmission Gear ratios: 1st 2nd 3rd 4th 5th 6th	Chain 6-speed, return 2.929 (41/14) 2.056 (37/18) 1.619 (34/21) 1.333 (32/24) 1.154 (30/26) 1.037 (28/27)	
Primary reduction ratio Final reduction ratio Clutch type (Primary)	2.029 (69/34) 3.429 (48/14) (USA/CAN/IDN) 2.867 (43/15) (PHL) Wet multi-disc, manual	

FRAME				
Туре			Trellis, high-tensile steel	
Suspension: F	ront	ZX400P	ø37 mm inverted fork (SFF-BP) with top-out springs	
		ZX400R/S	ø37 mm inverted fork (SFF-BP) with spring preload adjustability, and top-out springs	
F	Rear	ZX400P/R	Horizontal Back-link, gas-charged shock with	
		ZX400S	spring preload adjustability Horizontal Back-link, BFRC lite gas-charged shock with piggyback reservoir, compression and rebound damping and spring preload adjustability, and top-out spring	
	Front Rear	ZX400P/R ZX400S	120 mm 112 mm 124 mm	
Caster (Rake angle)			23.5°	
Trail Steering angle (left/right)			97 mm 35° / 35°	
Tyre: F	Front (Rear		120/70ZR17M/C (58W) 160/60ZR17M/C (69W)	
Brakes: Front Type			Dual semi-floating ø290 mm discs	
Caliper			(Effective diameter: ø257 mm) Dual radial-mount, monobloc, opposed 4-piston	
Rear Type			Single ø220 mm disc	
Caliper			(Effective diameter: ø186 mm) Single-piston	

Sport-Focused Edition: Ninja ZX-4RR

In addition to original KRT-inspired colour and graphics with "RR" naming, the sporty Ninja ZX-4RR features a higher-grade front fork with adjustable spring preload, and a high-grade Showa BFRC lite rear shock – the same type as the Ninja ZX-10R.



- * Accessories equipped on the Ninja ZX-4RR include:
- Dual-direction KQS

KAWASAKI TECHNOLOGY

















COLOUR

* Lime Green / Ebony







The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Kawasaki Motors, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colours may vary by market.